

Amendments to the Claims

1. (currently amended) The apparatus according to claim 61 wherein the cassette is operative to hold currency of different sizes therein

~~An apparatus including:~~

~~a cassette;~~

~~wherein the cassette is adapted for use in an automated banking machine;~~

~~wherein the cassette is operative to hold media therein;~~

~~wherein the cassette includes an adjustable rail system;~~

~~wherein the rail system is adjustable in size to respectively
correspond to media of different sizes;~~

~~wherein the rail system includes at least one rail assembly;~~

~~wherein a rail assembly includes a rail and a cap;~~

~~wherein the rail assembly is operative to include at least
one spacer.~~

2-44. (canceled)

45. (currently amended) The apparatus according to claim ~~46~~ wherein the cassette is operative to
hold currency of different sizes therein ~~+ wherein the rail and cap are operatively connected.~~

46. (currently amended) ~~The apparatus according to claim 45~~ Apparatus including:

a cassette,

wherein the cassette is adapted for use in an automated banking machine,

wherein the cassette is operative to hold media therein,

wherein the cassette includes an adjustable rail system,

wherein the rail system is adjustable in size to respectively
correspond to media of different sizes,

wherein the rail system includes at least one rail assembly,

wherein a rail assembly includes a rail and a cap,

wherein the rail assembly is operative to include at least
one spacer,

wherein the cassette includes a at least one fastener, wherein the at least
one fastener connects the rail and cap.

47. (previously presented) The apparatus according to claim 46 wherein the rail and cap both include at least one aperture.

48. (currently amended) The apparatus according to claim 47 wherein a fastener of the at least
one fastener extends through apertures to connect the rail and cap.

49. (previously presented) The apparatus according to claim 48 wherein the fastener extends through a rail aperture aligned with a cap aperture to connect the rail and cap.

50. (currently amended) The apparatus according to claim 46 wherein a fastener of the at least
one fastener comprises cantilever tabs.

51. (previously presented) The apparatus according to claim 46 wherein the rail assembly includes at least one spacer, wherein the spacer is intermediate the rail and cap.

52. (previously presented) The apparatus according to claim 51 wherein the rail and spacer and cap each include at least one aperture.

53. (currently amended) The apparatus according to claim 52 wherein a rail aperture, a spacer aperture, and a cap aperture are each aligned, wherein a fastener of the at least one fastener extends through the aligned apertures to connect the rail, spacer, and cap.

54. (currently amended) ~~The apparatus according to claim 1~~ Apparatus including:

a cassette,

wherein the cassette is adapted for use in an automated banking machine,

wherein the cassette is operative to hold media therein,

wherein the cassette includes a cassette lid,

wherein the cassette includes an adjustable rail system,

wherein the rail system is operatively connected to the cassette lid,

wherein the rail system is adjustable in size to respectively
correspond to media of different sizes,

wherein the rail system includes at least one rail assembly,

wherein a rail assembly includes a rail and a cap,

wherein the rail assembly is operative to include at least
one spacer.

55. (previously presented) The apparatus according to claim 54 wherein the rail system includes two rail assemblies, and wherein each rail assembly includes a rail, a cap, and at least one spacer therebetween.

56. (currently amended) The apparatus according to claim 54 † wherein the cassette is operative to hold currency of different sizes therein.

57. (currently amended) ~~The apparatus according to claim 1 and further including~~ Apparatus
including:

a plurality of different dimensioned rails, caps, and spacers, and

a cassette,

wherein the cassette is adapted for use in an automated banking machine,

wherein the cassette is operative to hold media therein,

wherein the cassette includes an adjustable rail system,

wherein the rail system is adjustable in size to respectively

correspond to media of different sizes,

wherein the rail system includes at least one rail assembly,

wherein the rail assembly includes at least one spacer

intermediate a rail and cap.

58. (previously presented) The apparatus according to claim 54 wherein the rail system includes a plurality of rail assemblies.

59. (previously presented) The apparatus according to claim 58 wherein at least one rail assembly includes at least one spacer intermediate a rail and cap, and wherein at least one other rail assembly includes a rail and cap without a spacer.

60. (previously presented) The apparatus according to claim 58 wherein each rail assembly includes at least one spacer intermediate a rail and cap.

61. (currently amended) ~~The apparatus according to claim 1~~ Apparatus including:

a cassette,

wherein the cassette is adapted for use in an automated banking machine,

wherein the cassette is operative to hold media therein,

wherein the cassette includes an adjustable rail system,

wherein the rail system is adjustable in size to respectively
correspond to media of different sizes,

wherein the rail system includes at least one rail assembly,

wherein a rail assembly includes a rail and a cap,

wherein the cap is operative to engage media in the
cassette,

wherein the rail assembly is operative to include at least
one spacer.

62. (previously presented) An apparatus including:

a first rail assembly, wherein the first rail assembly includes a removably
connected rail and cap, and wherein the first rail assembly is operative to include
at least one spacer connected intermediate the rail and the cap,

a second rail assembly, wherein the second rail assembly includes a removably
connected rail and cap, and wherein the second rail assembly is operative to
include at least one spacer connected intermediate the rail and the cap,

wherein the first rail assembly and the second rail assembly differ in size,

an automated banking machine currency cassette,

wherein the cassette is operative to hold a first sized currency and a second sized currency, wherein the first sized currency and the second sized currency differ in size,

wherein the first rail assembly is operative to engage the first sized currency but not the second sized currency,

wherein the cassette includes a cassette lid,

wherein the cassette lid is operatively connectable to each of the first and second rail assemblies.

63. (previously presented) A method including:

- (a) fastening together a rail and a cap of an automated banking machine media cassette, wherein the fastening results in the cassette having a rail assembly of a first size;
- (b) fastening together a rail and a cap of the cassette, wherein the fastening results in the cassette having a rail assembly of a second size, wherein the second size differs from the first size.

64. (previously presented) The method according to claim 63 wherein the rail assembly of (b) is a reconfiguration of the rail assembly of (a).

65. (previously presented) The method according to claim 63 wherein (a) includes fastening at least one spacer intermediate the rail and the cap.

66. (previously presented) The method according to claim 65 wherein (b) includes fastening at least one spacer intermediate the rail and the cap.

67. (previously presented) The method according to claim 63 wherein subsequent to (a) and prior to (b), further including

(c) engaging media in the cassette with the rail assembly.

68. (previously presented) The method according to claim 67 wherein the media comprises currency, and wherein (c) includes engaging currency in the cassette with the rail assembly.

69. (previously presented) The method according to claim 68 wherein (c) includes engaging currency in the cassette with the cap.

70. (previously presented) The method according to claim 68 wherein (a) includes fastening together the rail and the cap with a fastener having cantilever tabs.

71. (currently amended) The method according to claim 70 ~~69~~ wherein (a) includes extending the fastener through a rail aperture aligned with a cap aperture.

72. (previously presented) The method according to claim 63 wherein the cassette includes a cassette lid, wherein (a) includes operatively connecting the rail assembly to the lid.

73. (previously presented) The method according to claim 72 wherein the rail assembly of (b) includes the rail and cap of the rail assembly of (a).